NRE 65/160 B/A - 5,5

CLOSE COUPLED INLINE PUMP



SUBMITTAL

JOB	REPRESENTATIVE
	ORDER NO. DATE
ENGINEER	SUBMITTED BY DATE
CONTRACTOR	APPROVED BY DATE

PUMP DES	SIGN DATA
NO. OF PUMPS	
TAG:	
CAPACITY: 42 m³/h	
HEAD: 25 mWC	
LIQUID: WATER	VISCOSITY:
TEMPERATURE: 120 °C	SPECIFIC GRAVITY:

MATERIALS OF CONSTRUCTION			
SHAFT	CHROME-NICKEL STEEL AISI303		
IMPELLER	CAST IRON		
CASING	CAST IRON		
SEALING	CARBON-CERAMIC-NBR		

	MOTOR DE	SIGN DATA	
kW : 5,5		RPM: VFD	
FRAME SIZE:		ENCLOSURE:	
PROTECTION CLAS	SS:	IP55	
VOLTS: 400	HERTZ: 50	PHASE: 3	
BUILT-ON MOTOR			
FREQUENCY INVE	RTER MOUNTI	ED ON MOTOR	

DIMENSIONS					
DNs	DNd	а	f	h1	
65	65	340	552	105	
h2	I	I1	12	x	
447	160	121	142	125	







